

L25 R S7 REMOTE CONTROL



15 HP
HORSE POWER



**NEW INTUITIVE
REMOTE CONTROL
WITH LCD SCREEN**

L25 R SERIES 7 New redesigned 3 heads professional planetary floor grinder **400-480V 3 phase Motor 11KW-15HP. New Remote Control System with LCD screen.** Wide working width **680mm**, heavy grinder with **total weight 515Kg**. Suitable for heavy duty works, floor preparation, coatings removal, grinding and polishing Concrete, Marble, Terrazzo, Granite and natural stone. **New sealed and Dust-proof planetary head** with no chain tensioner, stronger timing belt and upgraded bearings. **Integrated adjustable weights system in 4 positions** for easy balance. New heavy duty rubber tires with redesigned transport wheel for easy transport and loading (included). The best choice for professionals. Equipped with **special battery system** which allows you to move the machine on site without connecting the electric cable. This also simplifies the loading and unloading operations. Cable 17.5m included



WORKING WIDTH Ø 680mm



NEW SEALED & DUST-PROOF GRINDING HEAD

- Completely redesigned chain-driven planetary drive with no chain tensioner.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.



NEW REMOTE CONTROL WITH LCD SCREEN

Precise control over the machine two sensitive thumbsticks control its position and offset, including integrated mapping on the offset. A wide range of functions. Light and easy to use with ergonomic rubber grip. RC Battery (rechargeable). Battery charger included.



L25 R S7 REMOTE CONTROL



MORE TORQUE. BETTER CONTROL. LESS MAINTENANCE

Redesigned transport wheel
for easy transport and loading (included)

Multiple positions handle
for faster adjustability

3 Led lights with
magnetic attachment

New Reinforced frame width updated weights
and handle for better operator experience



L25 R S7 PRODUCTIVITY RATES* - Sqm/H

Grinding and Polishing Concrete 7 Step	25 - 30
Floor Preparation 1 Step	100 - 130
Polishing Terrazzo 5 Step	30 - 40
Resin, varnish and coating removal 1 Step	100 - 150
Grinding and Polishing Marble 5 Step	20 - 30
Grinding and Polishing Granite 7 Step	9 - 12

*production rates may vary according to the surface conditions,
diamond tools used, equipments, operator, etc.

L25R S7 TECHNICAL DATA

Power	11 Kw - 15 Hp	Tool connection	Quick Change
Working Width	680 mm	Tool holder diameter	3 x 235 mm / 9"
Voltage	400-480 V - 50/60 Hz	Application	Wet / Dry
Weight	515 Kg	Dust-vacuum	Yes
Amperage	Max 30 Amp	Water Tank capacity	20 Lt
Tool Holder RPM	400 - 1100 rpm	Code	L25RS7